

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1. Product identifier

Product name **FRAG REFILL DAVANIA 6X150ML**  
 Product No. **575523**

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses **Air Freshener**

### 1.3. Details of the supplier of the safety data sheet

Selden Research Limited t : 01298 26226  
 Staden Lane f : 01298 26540  
 Ashbourne Road e : safety@selden.co.uk  
 Buxton  
 Derbyshire  
 SK17 9RZ  
 United Kingdom

### 1.4. Emergency telephone number

01298 26226

## SECTION 2: HAZARDS IDENTIFICATION

### 2.1. Classification of the substance or mixture

Classification (67/548/EEC) **F+;R12.**

### 2.2. Label elements

Labelling



Extremely Flammable

Risk Phrases

R12 Extremely flammable.

Safety Phrases

A1 Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use., A2 Do not spray on a naked flame or any incandescent material.  
 S2 Keep out of the reach of children.  
 S9 Keep container in a well-ventilated place.  
 S16 Keep away from sources of ignition - No smoking.  
 S23 Do not breathe vapour/spray., P14 Contains (L) Hexyl Cinnamyl, Butylphenyl methylpropional, coumarin. May produce an allergic reaction.  
 S51 Use only in well-ventilated areas.  
 S46 If swallowed  
 Seek medical advice immediately and show this container or label.

### 2.3. Other hazards

No other hazards known

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1. Substances

Not Applicable

### 3.2. Mixtures

(L) Hexyl Cinnamyl		0.5-1%
CAS-No.: 101-86-0	EEC (EINECS) No. 202-983-3	
Classification (EC 1272/2008)		Classification (67/548/EEC)
Skin irritation, category 2 - H315		Xi;R38

Skin sensitisation, categories 1, 1A, 1B - H317		R43
60-100%		
BUTANE	EEC (EINECS) No. 203-448-7	
CAS-No.: 106-97-8		
Classification (EC 1272/2008)		Classification (67/548/EEC)
Flammable liquids, category 1 - H224		F+;R12
0.5-1%		
Butylphenyl methylpropional	EEC (EINECS) No. 201-289-8	
CAS-No.: 80-54-6		
Classification (EC 1272/2008)		Classification (67/548/EEC)
Acute toxicity, category 4 - Oral - H302		Xn;R22
Reproductive toxicity, categories 2 - H361		;R62
Skin irritation, category 2 - H315		Xi;R38
Hazardous to the aquatic environment, chronic, category 2 - H411		N;R51/53
Hazardous to the aquatic environment, chronic, category 2 - H411		R43
Skin sensitisation, categories 1, 1A, 1B - H317		Repr. Cat. 3
0.5-1%		
coumarin	EEC (EINECS) No. 202-086-7	
CAS-No.: 91-64-5		
Classification (EC 1272/2008)		Classification (67/548/EEC)
Acute toxicity, category 4 - Oral - H302		Xn;R22
Skin sensitisation, categories 1, 1A, 1B - H317		R43
5-10%		
ETHANOL	EEC (EINECS) No. 200-578-6	
CAS-No.: 64-17-5		
Classification (EC 1272/2008)		Classification (67/548/EEC)
Flammable liquids, category 2 - H225		F;R11
0.5-1%		
Ethylene brassylate	EEC (EINECS) No. 203-347-8	
CAS-No.: 105-95-3		
Classification (EC 1272/2008)		Classification (67/548/EEC)
Hazardous to the aquatic environment, chronic, category 2 - H411		N;R51/53
Hazardous to the aquatic environment, chronic, category 2 - H411		

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of first aid measures

#### General information

Inhalation	Move the exposed person to fresh air at once., Keep the affected person warm and at rest. Get prompt medical attention.
Ingestion	Rinse mouth thoroughly., Drink plenty of water., Get medical attention.
Skin contact	Wash the skin immediately with soap and water., Get medical attention if any discomfort continues.
Eye contact	Spray in the eyes:., Promptly wash eyes with plenty of water while lifting the eye lids., Continue to rinse for at least 15 minutes., Get medical attention if any discomfort continues.

### 4.2. Most important symptoms and effects, both acute and delayed

Inhalation	May cause irritation to the respiratory system., Vapours may cause headache, fatigue, dizziness and nausea., Prolonged inhalation of high concentrations may damage respiratory system.
Ingestion	May cause burns in mucous membranes, throat, oesophagus and stomach., May cause stomach pain or vomiting.
Skin contact	Prolonged or repeated exposure may cause severe irritation., Acts as a defatting agent on skin. May cause cracking of skin, and eczema.
Eye contact	Irritation of eyes and mucous membranes.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat Symptomatically.

## SECTION 5: FIREFIGHTING MEASURES

### 5.1. Extinguishing media

Extinguishing media Use:., Powder., Dry chemicals, sand, dolomite etc., Water spray, fog or mist.

### 5.2. Special hazards arising from the substance or mixture

Unsuitable extinguishing media

### 5.3. Advice for firefighters

Special Fire Fighting Procedures

Self contained breathing apparatus and full protective clothing must be worn in case of fire. Containers close to fire should be removed or cooled with water., Use water to keep fire exposed containers cool and disperse vapours.

**SECTION 6: ACCIDENTAL RELEASE MEASURES**

6.1. Personal precautions, protective equipment and emergency procedures

For personal protection, see section 8.

6.2. Environmental precautions

Any spillage needs to be contained and not allowed to enter water courses

6.3. Methods and material for containment and cleaning up

Wear necessary protective equipment., Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate., If leakage cannot be stopped, evacuate area.

**SECTION 7: HANDLING AND STORAGE**

7.1. Precautions for safe handling

Keep away from heat, sparks and open flame., Avoid spilling, skin and eye contact., Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

7.2. Conditions for safe storage, including any incompatibilities

Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

7.3. Specific end use(s)

See product label for detailed usage and instructions.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

8.1. Control parameters

Name	STD	TWA - 8 Hrs	STEL - 15 Min	Notes
BUTANE	WEL	600 ppm1450 mg/m3	750 ppm1810 mg/m3	
ETHANOL	WEL	1000 ppm1920 mg/m3		

WEL = Workplace Exposure Limits

8.2. Exposure controls

Protective equipment



Engineering measures

Provide adequate general and local exhaust ventilation.

Hand protection

Use protective gloves.

Eye protection

Wear approved safety goggles.

Other Protection

General workwear only

Hygiene measures

DO NOT SMOKE IN WORK AREA!

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

9.1. Information on basic physical and chemical properties

Appearance	Aerosol.
Odour	fragrant
Comments	Information given relates to total aerosol container contents.
Flash point (°C)	- 74
Auto Ignition Temperature (°C)	+ 405
Flammability Limit - Upper(%)	1.8

Flammability Limit - Lower(%) 10.0

## SECTION 10: STABILITY AND REACTIVITY

### 10.1. Reactivity

Stable under normal temperature conditions.

### 10.2. Chemical stability

Stable under normal temperature conditions.

### 10.3. Possibility of hazardous reactions

None known

### 10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition.

### 10.5. Incompatible materials

No incompatible groups noted.

### 10.6. Hazardous decomposition products

Fire creates: , Toxic gases/vapours/fumes of: , Carbon monoxide (CO) , Carbon dioxide (CO<sub>2</sub>).

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on toxicological effects

Toxicological information	No toxicological data is available for this mixture, however data can be provided for specific raw materials upon request.
Inhalation	May cause irritation to the respiratory system. , Vapours may cause headache, fatigue, dizziness and nausea. , Prolonged inhalation of high concentrations may damage respiratory system.
Ingestion	May cause burns in mucous membranes, throat, oesophagus and stomach. , May cause stomach pain or vomiting.
Skin contact	Prolonged or repeated exposure may cause severe irritation. , Acts as a defatting agent on skin. May cause cracking of skin, and eczema.
Eye contact	Irritation of eyes and mucous membranes.

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

The product is not expected to be toxic to aquatic organisms.

### 12.2. Persistence and degradability

Degradability The product is expected to be biodegradable.

### 12.3. Bioaccumulative potential

Bioaccumulative potential The product does not contain any substances expected to be bioaccumulating.

### 12.4. Mobility in soil

Mobility: The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces.

### 12.5. Results of PBT and vPvB assessment

This product does not contain any PBT or PvB substances

### 12.6. Other adverse effects

None known

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

Empty containers must not be burned because of explosion hazard., Dispose of waste and residues in accordance with local authority requirements.

## SECTION 14: TRANSPORT INFORMATION

General LIMITED QUANTITIES for ADR/RID/IMDG. (Not for transportation via air (ICAO/IATA) as Limited Quantities)

### 14.1. UN number

UN No. (ADR/RID/ADN)	1950
UN No. (IMDG)	1950
UN No. (ICAO)	1950

### 14.2. UN proper shipping name

Proper Shipping Name: AEROSOLS, FLAMMABLE

### 14.3. Transport hazard class(es)

ADR/RID/ADN Class	2
IMDG Class	2.1
ICAO Class/Division	2.1
Transport Labels	Not Applicable

### 14.4. Packing group

### 14.5. Environmental hazards

Environmentally Hazardous substance/Marine Pollutant No

### 14.6. Special precautions for user

Tunnel Restriction Code n/a

## SECTION 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

UK Regulatory References	The Control of Substances Hazardous to Health Regulations 2002 (S.I 2002 No. 2677) with amendments.
Environmental Listing	Rivers (Prevention of Pollution) Act 1961., Control of Pollution (Special Waste Regulations) Act 1980.
Statutory Instruments	Control of Substances Hazardous to Health., The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716).
Approved Code Of Practice	Classification and Labelling of Substances and Preparations Dangerous for Supply.
Guidance Notes	Workplace Exposure Limits EH40., Introduction to Local Exhaust Ventilation HS(G)37., CHIP for everyone HSG (108).
EU Legislation	System of specific information relating to Dangerous Preparations. 2001/58/EC., Dangerous Preparations Directive 1999/45/EC., Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments., Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments.
National Regulations	The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2007 (CDG 2007).

### 15.2. Chemical Safety Assessment

No chemical assessment has been carried out as this Safety Data Sheet is for a mixture

## SECTION 16: OTHER INFORMATION

## General information

The following risk phrases relate to the raw materials in the product and not the product itself:-

## Revision Comments

Safety Data Sheet revised to be in accordance with EU Regulation No 453/2010 - REACH Regulations.

Revision Date 20/05/2013

Revision 1

## Risk Phrases In Full

R12 Extremely flammable. | R11 Highly flammable | R43 May cause sensitisation by skin contact. , R38 Irritating to skin. | R22 Harmful if swallowed. , R43 May cause sensitisation by skin contact. | R43 May cause sensitisation by skin contact. , R22 Harmful if swallowed. , R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. , R62 Possible risk of impaired fertility. , R38 Irritating to skin. | R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. |

## Hazard Statements In Full

H224 Extremely flammable liquid and vapour.  
H225 Highly flammable liquid and vapour.  
H302 Harmful if swallowed.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H361 Suspected of damaging fertility or the unborn child .  
H411 Toxic to aquatic life with long lasting effects.